

# **Product Information**

Batch mixer CM-1000-E

# atch Mixer $\mathsf{CM}$



Image similar

# **Application areas:**

- Micro tunnelling, pipe jacking
- Anchor injection, Ground stabilization, Rock injection
- Drill injection
- Jet grouting, Pipe roof grouting
- Floor level injection
- Cavity filling

### Mixing of:

- Cement slurries
- Anchor grout
- Bentonite slurries
- · Filling material for peripheral sealing
- Insulation slurries
- · Fly-ash slurries

Technical Data / Performance Data\*

Mixing capacity (with 20 batches/h)	20	m3/h
Effective volume mixer	1000	1
Mixing water minimum	350	1
Mixer filling level (bag loading)	1150	mm
Solids grain size	max. 2	mm
Dosage liquid	3"	ball valve, manually
Level indicator (rough)	350 – 1000	I; filling bar adjustable
Dosage solids	manually	bag loading grid
Mixer outlet	Storz B	3" standard coupling DIN 14307, alternatively 3" IG
Water connection	Storz B	3" standard coupling DIN 14307, max.6 bar
Cleaning connection	DN 20	Geka-claw coupling
Power connection	CEE-plug	63 A, 5-pole
Power input	22	KW
Voltage	400	V; 50 Hz
Dimensions	2,2 x 1,8 x 2,2	m (LxWxH)
Weight	approx.1100	kg

)\*The specified performance data are non-binding values that differ significantly depending on dosing, mixing and discharge

**GERTEC**Maschinen- und Anlagenbau
GmbH

Ludwig-Prandtl-Str. 1 D-87448 Waltenhofen

Fax: 08303-929509-99 Phone: 08303-929509-0 info@gertec-gmbh.de

Art.No.: 36234 Edition: 2022-05-25 Technical specifications are subject to change Page 1 / 2



# **Produktinformation**

**Batch Mixer CM-1000-E** 

## **Description:**

The batch mixer CM-1000-E (manual operation) is an especially for construction site use developed compact slurry mixer for processing of bagged goods. It is particularly suitable for mixing bentonite - and cement slurries, diaphragm wall compounds or other solids-containing suspensions.

### **Characteristics:**

- Processing of bagged goods
- Easy operating, maintenance and cleaning
- Minimum installation and commissioning effort
- Optimal mixing quality (colloidal mixer)
- Low space required
- Easy operation (crane, lift truck, forklift)
- Low operating costs

### **Features:**

- ✓ Colloidal mixer CM-1000 for colloidal processing of slurries
- ✓ Water dosage DN 80 with hand-operated ball valve
- ✓ Level indicator (rough) via adjustable filling bar
- ✓ Recirculation and emptying line (easy uncoupling) with 3-way valve
- ✓ Base frame galvanized, lift truck handling is possible from the long or front sides, forklift handling of the faces,
- ✓ Electrical control for mixer drive
- ✓ Electrical input

### Accessories / Equipment Version (not in delivery included):

- Water meter
- Water tank
- Mixing scale

### **GERTEC**

Maschinen- und Anlagenbau GmhH

> Ludwig-Prandtl-Str. 1 D-87448 Waltenhofen

Fax: 08303-929509-99 Phone: 08303-929509-0 info@gertec-gmbh.de

Art.No.: 36234 Edition: 2022-05-25 Technical specifications are subject to change Page 2 / 2